

KODAK PROFESSIONAL Inkjet Photo Paper, Lustre / 255g

Next-generation paper for accurate color reproduction **FEATURES:**

The latest printer and ink technology

KODAK PROFESSIONAL Inkjet Photo Paper, Lustre has been updated to take advantage of the wider color gamut and improved ink technology of the latest generation of wide format inkjet printers from Canon, Epson and HP.

Accurate reproduction

This next-generation paper has a larger color gamut and higher Dmax to ensure that color captured in-camera reproduces more accurately, while producing deeper, richer black, an expanded dynamic range and additional detail in shadow areas.

ArtSure Certification

ArtSure Certification ensures the highest standards for fine art prints giving art collectors and artists confidence and validity in limited edition print runs.

APPLICATIONS:

- Wedding, portrait, landscape and exhibition photography
- High-end retail and display graphics
- · Corporate and home décor



- Expanded color gamut and higher Dmax
- Designed to take advantage of the latest printer and ink technology
- · Engineered to lay flat with little to no curl
- ArtSure Certification certifies testing for archival properties of lightfastness and permanence

US Size	Euro Size	Quantity	SKU
8.5″ x 11″	20,08 cm x 29,72 cm	50 Sheets	KPRO8511L
13″ x 19″	33,02 cm x 48,26 cm	20 Sheets	KPRO1319L
*(A4) 8.3" x 11.7″	20,08 cm x 29,72 cm	50 sheets	KPROA4L
*(A3+) 13" x 19"	33,02 cm x 48,26 cm	20 sheets	KPROA3+L
10" x 100'	25,4 cm x 30,5 m	1 Roll	KPRO10L
16" x 100'	40,64 cm x 30,5 m	1 Roll	KPRO16L
17" x 100'	43,2 cm x 30,5 m	1 Roll	KPRO17L
24" x 100'	61,0 cm x 30,5 m	1 Roll	KPRO24L
36" x 100'	91,4 cm x 30,5 m	1 Roll	KPRO36L
44" × 100'	111,8 cm x 30, 5 m	1 Roll	KPRO44L
60" x 100'	152,4 cm x 30,5 m	1 Roll	KPRO60L

KODAK PROFESSIONAL Inkjet Photo Paper I / 255g

Properties	Specifications	
Material	Resin-coated photo base	
Gauge	10 mil / 255g	
Gloss Level	>/=25	
Opacity	>90%	
Whiteness	>134	
Tear Strength	NA	
Printer/Ink Compatibility	Compatible with Noritsu, Fuji and Epson Dry Lab printers.	
Software Setting	The photo satin/luster paper setting in most RIPs is appropriate; however, we recommend a custom ICC profile for optimal results. Please refer to <u>KodakWFMedia.com</u> for ICC profiles for some printers.	
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.	
Finishing/Post Processing	It is always recommended that a protective laminate be applied after printing. Hand applying laminate is not recom- mended. Pressure-sensitive or thermal laminates can be used. Before applying the laminate, allow the image to dry for 24 hours.	
Optimal Service Environment	72° F (21° C), 50% R.H. For end use: 0-300° F.	
Handling Recommendations	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.	
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.	
Shelf Life	1 year from the BMG ship date when stored in proper conditions.	



BRANDmanagement GROUP

AMS:888-893-4668EMEA:+34 935 479 700APJ:+61 2 8038 5013

KodakWFMedia.com

The Kodak trademark, logo, and trade dress are used under license from Kodak.

© 2017, Brand Management Group

